

Planning sheet: Optimyst Revive in an existing fireplace opening


For the framer, electrician, plumber and finisher. Every figure is Dimplex's, from the document named in the Sources row; where a figure is not on file the row says so and we confirm it at the site visit. This sheet is a planning aid; the manual governs.

Sheet v1 · August 2026

Planning aid, not a permit drawing

FRONT ELEVATION, TO SCALE (overall unit size, not the framed opening)

Revive 25 in insert · ABN15-RGB-AM



overall 25-1/4 × 24-15/16 × 12-13/16 in
minimum opening 25-1/4 wide × 25 high × 12 deep in

Frame to the manual's framing/opening table, never to the overall size.
Every unit needs its stated fresh-air path, a water method and a 120 V circuit (240 V option on the Linear).

MSRP (CAD, June 2026 list)	Revive 25 in insert: \$2,699.99 · order no. 500003863
Overall unit size	Revive 25 in insert: 25-1/4 × 24-15/16 × 12-13/16 in
Opening / framing	Revive 25 in insert: minimum opening 25-1/4 wide × 25 high × 12 deep in (Revive installation manual R00)
Electrical	Revive 25 in insert: 120 V; 1,250 W; 10.42 A; hardwired, 3-wire, into the opening; circuit: 15 A dedicated recommended; required if the breaker trips with the heater on (manual)
Heat	Revive 25 in insert: yes: fan-forced heater, on demand, up to 1,000 sq ft (sell sheet); flame-only mode for the rest of the year
Water	Revive 25 in insert: pull-out drawer with a refillable tank; filtered or decalcified water; a softener is recommended in hard-water areas (manual); Calgary is one; run time: not stated in the documents on file
Fresh air	Revive 25 in insert: the air inlet under the drawer must stay clear; an extra 16 in² path to the underside of the unit is recommended for the best flame
Clearances and placement	Revive 25 in insert: the chimney must be professionally cleaned and blocked off before the insert goes in (manual); keep it out of drafts. Above: heated unit: follow the television maker's guidance for mounting over a heater
Cleaning	Revive 25 in insert: top cover, reservoir, tank and transducer cleaned with soap and water at least once a month; more often with hard water (manual)
Accessories on the price list	Revive 25 in insert: Revive 36 × 32 in trim kit (REV36X32, \$262.99); Revive 40 × 35 in trim kit (REV40X35, \$272.99)
Confirm at site visit	Revive 25 in insert: BTU output (not printed); tank capacity and run time; weight
Sources	Revive 25 in insert: Optimyst Revive installation manual R00; Revive three-part specification; Revive sell sheet; Dimplex CAD price list June 2026; manual: sites/g/files/emiian436/files/2025-02/7216930100R00_EN%20Rev...